Motor ID no.		Facility			OUSEN SOURCE PROPERTY				Date				
Manufacturer Frame size		Model		_	Type				Serial no.				
Frame size Hp / kW		Enclosure		_	Voltage				RPM				
Code letter		Full-load amps Design letter			200	Full-load efficiency (%) Insul. class				☐ 1 phase ☐ 3 phase Motor weight			
DE bear		receie ell	ODE bearing no.			Application(s)			IVIC	IVIOLOT WEIGHT			
	stalled		Baseline data			-	Vibration spectra			Ali	Alignment data		
No-load	amps		☐ Yes ☐				Yes □				☐ Yes ☐ No		
		atus □ New	Repaire	ed 🗆 Stor	age	Mo	otor loca	tion					
	for replace	ment		183						60-			
Repair h													
Comme	nts (if any)	AND COMME	1/2 HT 1000		in the same	in the second	ling of	ide d	transmin	ha or			
□ Dama □ Lubrio	aged or miss cant leakag	0.		□ Exterio	or paint coaprotective of	coatin	g deficie	nt	□No	aft block visible d		or inadequate	
NSULAT	TION RESIS	STANCE TES	ST □ N/A	□ N/P		WINDING RESISTANCE TEST \(\sigma N/A \) \(\sigma N/P \)							
Result	Result Test voltage		Resistance (megohms)		gohms)	Resistance (indica							
□ Pass	i i borcal	ica enide	1-mi	n	_ ΜΩ	I -	Result		_eads 1 - 2		ads 2 - 3	Leads 3 -	
☐ Fail	\	/olts DC	10-m	nin	_ΜΩ		☐ Pass	-		_			
IFI ECT	RIC ARSO	RPTION RAT	IO TEST		N/P	-	☐ Fail		Ω □ mΩ ads_identify le		Ω ImΩ	□Ω □m9 5, 2-4, 3-5, etc.)	
Result		ec (DAR)		dition	1N/1"		ii more th	ا ک الد	aus, iueriiity le	аи соппес	ผบกร (e.g., 1-6	o, ∠-4, ડ-5, etc.)	
□ Pass		< 1.1 Poor				1005005115							
☐ Fail		1.1 to 1.24		Questionable			ACCESSORIES TESTS N/A N/P Working Device type						
		1.25 to 1.3 1.4 to 1.6		Fair Good			Working Device type ☐ Yes Space heaters						
	1.4 to 1.6 > 1.6		Excellent			☐ No							
Measure in	nsulation resis	tance (IR) at 30	seconds and		with a digital		ייים דוור	OLIA -	T EVTENC	ON 5	IOUT TO	(A	
neter. Divi	iue 60-second	reading by 30-se	cond reading.				Result		-T EXTENSI naft extensi		IOUT DN/		
IGH-PC	TENTIAL T	TEST N/	A □ N/P			-	Pass				Measure	e with a dial	
Result		Itage (indicate	AC or DC)				☐ Fail		Rett Life Co.	(in or mr	n) "Idicator		
□ Pass □ Fail		Volts □ A	CDC			(DUTPUT	SHAF	T EXTENSION	ON DIAM	ETER 🗆 N	I/A □N/P	
_ rall		10113 🗆 /	.000		1131101000		Result		aft extension		tor		
URGE 1	TEST 🗆	N/A □ N/P					Pass			in or mm	otor	with a micron	
Result	Test vo						☐ Fail		(in or mm)		
☐ Pass		\/ali-				Static test comments (if any)							
☐ Fail		Volts						0. 0011	milionio (ii ai	.,,			
INGI F-	PHASE BO	TOR TEST	□N/A □	1 N/P									
Result	Current) (max. / min.))								
☐ Pass	Max.			- v-oses / (IIII)	,								
☐ Fail	Min					N	lote: N/A	means	"not annlicat	ole: N/P n	neans "not per	formed	
		sheet – co	I/P nstallation In service						ola	lation			
	rallel set		Installation			ings	Parallel offset p		RPM	Instal Mils	mm	In service Mils mi	
	rallel set gular		Installation			ouplings spacers	offset p	er	RPM				
sguid Ang	rallel set gular salignment	RPM N	Installation			Couplings w/spacers	offset p in of sp length	er	adama.				
sguid Ang	rallel set gular salignment		Installation			Couplings W/spacers	offset p in of sp length	er	All				
sp Par offs Offs And mis Soft foot	rallel set gular salignment	RPM N	Installation lils mm	n Mils		Soft f	offset p in of sp length foot OTOR C IBRATIO Vibration	ONLIN DN AN specikip vik	All NE) NALYSIS E tra taken: E oration meas tion velocity	N/A Care Suremen	mm I N/P I No ts below.)		
ss Par offs Offs And mis	rallel set gular salignment	RPM N	Installation lils mm	DYNAM	mm	Soft f	offset p in of sp length foot OTOR C IBRATIO Vibration	ONLIN specikip vibra	All NE) NALYSIS E tra taken: E oration meas tion velocity	Mils N/A [Yes [Suremen	mm I N/P I No ts below.)		
ss Par offs Offs And mis	rallel set gular salignment	RPM N	Installation lils mm	DYNAM	mm	Soft I	offset p in of sp length foot OTOR C (IBRATIC Vibration (If Yes, s)	ONLIN Specikip vib Vibra	All NE) NALYSIS [tra taken: [oration meas tion velocity sec mr e end/ om	N/A Care Suremen	mm I N/P I No ts below.) red in Opposite	Mils mi	
ss Par offs Offs And mis	rallel set gular salignment	RPM N	Installation lils mm	DYNAM	mm	Soft 1	offset p in of sp length foot OTOR C (IBRATIC Vibration (If Yes, s) Result	DNLIN Specikip viti Vibra Drive botto	All NE) NALYSIS [tra taken: [oration meas tition velocity sec mr e end/ om oontal	N/A Care Suremen	mm N/P No ts below.) ed in Opposite Horizonta	Mils mi	
Par offs offs of offs offs of offs offs of	rallel set gular salignment	RPM N	Installation lils mm	DYNAM	mm	Soft 1	offset p in of sp length foot OTOR C (IBRATIC Vibration (If Yes, s)	DNLIN Specikip vik Vibra In/s Drive botto Horiz	All NE) NALYSIS [tra taken: [oration meas tion velocity sec	N/A Care Suremen	mm N/P No ts below.) ed in Opposite Horizonta Vertical	Mils mi	
Par offs Angmis of the Control of th	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	mm	Soft 1	offset p in of sp length foot OTOR C (IBRATIC Vibration (If Yes, s) Result	DNLIN Specikip viti Vibra Drive botto	All NE) NALYSIS [tra taken: [oration meas tion velocity sec	N/A Care Suremen	mm N/P No ts below.) ed in Opposite Horizonta	Mils mi	
Par offs offs of offs of offs of offs offs	rallel set gular salignment t	RPM N	Installation lils mm	DYNAM Watts	mm	Soft f	offset pin of sp length foot OTOR C Vibration (If Yes, s Result	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Par offs Angmis of the Control of th	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft f	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm N/P No ts below.) ed in Opposite Horizonta Vertical	e drive end/to	
Build Anger Misson Miss	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Build Anger Misson Miss	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Build Anger Misson Miss	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Paring offs offs of offs of offs offs offs of	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Par offs offs of offs of offs of offs offs	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Par offs off off off off off off off off of	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive botto Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	
Par offs off off off off off off off off of	rallel set gular salignment t	All N/A NA Amps	Installation lils mm	DYNAM Watts	IIC TESTS	Soft to	offset pin of sp length foot OTOR C (IBRATIC Vibration (If Yes, s Pass Fail	DNLIN DN AN speciskip vith in/s Drive bottc Horiz Vertic Axial	All NE) NALYSIS [tra taken: [pration meas tion velocity sec	N/A [] Yes [surement measurm/sec	mm I N/P I No ts below.) ed in Opposite Horizonta Vertical Axial	e drive end/to	